

African Installer

Accommodation Support Barge



African Installer provides support and infrastructure during offshore construction or modification and maintenance. Flat bottom barges are well suited for the calm waters off the coast of Africa, Middle East and many other geographies.

African Installer can also provide lay-down areas. The barge is catenary anchored and will typically be moored in benign waters, and sometimes alongside the offshore platform, to which it will be connected with a gangway, for safe personnell transfer.

AOS

African Offshore Services

Accommodating the Offshore Industry



Accommodation barge African Installer

Technical Specifications

MAIN PARTICULARS

BUILT

Year:	2008
Builder:	Jaya - Batam
Class:	ABS
Flag:	Republic of Cyprus
Port of registry:	Limassol
Official no.:	711409
Sign call:	5BLK2

DIMENSIONS

Length overall:	100,58 m
Beam:	31,70 m
Depth:	7,31 m
Maximum draft:	4,5 m
Deadweight:	8 494,53 MT
Displacement (lightship):	5 647 MT
Gross tonnage:	9 462 t
Net tonnage:	2 838 t

ACCOMMODATIONS

Accommodations for:	300 persons
Single cabins:	8
2 man cabins:	14
4 man cabins:	66
Fully air conditioned, comply to ILO 92, IMO Resolution A468 (xll)	

CAPACITIES

Deck area:	1 600 m ²
Maximum deck cargo:	1 404 m ²
Deck strength:	17,5 t/m ²
Fuel oil:	1 739,1 m ³
Fresh water:	1 866,6 m ³
Ballast:	4 597,2 m ³

MACHINERY / PERFORMANCE

Generators:	5 x Caterpillar, 620 Kw each – total 3 100 Kw
Emergency generator:	1 x Caterpillar, 99 Kw
Fuel daily consumption:	3,5 m ³ (average)
Water makers:	2 x Stromme NWC3-60 – 60 m ³ /day each

DELIVERY RATES

Fuel oil:	1 x 118 m ³ / h @ 60 m head
Fresh water:	2 x 120 m ³ / h @ 60 m head
Ballast water:	2 x 500 m ³ / h @ 50 m head

EQUIPMENT & ELECTRONICS

DECK EQUIPMENT

8 point mooring	
Anchors:	7 x 10 MT each + 2 x 7 MT each
Wire cables:	8 x 52 mm – length 1 400 m
Main winches:	8 Mentrade winches, electro-hydraulic type
Tugger winches:	2 x 15 @ 20 m
Capstans:	4 x 10 MT @ 20 m
Main crane – pedestal:	Huisman Crane, SWL 300T
Helideck:	25,62 m x 25,62 m, 12 t max load, suitable for M18

SAFETY EQUIPMENT

Life saving equipment:	1 rescue boat Life rafts, 24 x 25 persons
Fire-fighting system:	Class II
Sprinkler system:	1
Fixed CO2 system:	Engine & Control room, Paint locker, Galley
Foam system for Helideck:	1 unit

RADIO COMMUNICATION & NAVIGATION EQUIPMENT

GMDSS:	1
VHF / DSC Radiotelephone:	1 x Furuno FM-8800S VHF DSC 1 x Furuno Air band VHF radio IC-A200
AIS:	1 x IRC HIS-183
Gyro Compass:	1
Echo Sounder:	1 x Furuno FE-700 Echo Sounder
GPS:	1 x Furuno GP90
Radar:	1 x Furuno I932MK2

Particulars are believed to be correct but not guaranteed. All figures given are approximate only. Owners reserve the right to amend the specifications without notification.